

UniSync™ T8 Linear

Ballast Compatible & Ballast Bypass

START LIGHTING



Project:

Type:

Catalog#:

Warranty / Certifications

- 5 Year Warranty
- UL listed for damp locations
- DLC qualified

Features & Benefits

- Integral driver in lamp
- Ballast Compatible AND Single or Double End Ballast Bypass
- 2835 chipset
- 50,000 hour lifespan
- Consumes up to 50% less energy than standard fluorescent
- Non-rotating ends are standard
- Minimized labor costs
- LM79/LM80/TM-21 data available
- Non-DLC rotating endcaps available. Consult factory
- Other custom wattages available. Consult factory

Description

START Lighting's **UniSync™** LED T8 lamps provide flexible installation for **non-ballasted single end OR double end wiring AND ballasted/plug-n-play configurations**. These popular retrofit lamps support both linear and U-bend applications.

Specifications

Model	Input (AC)	Freq. (Hz)	Watts	Lumens	CRI	Beam Angle	CCT (K)	Length	Cert.
HUT12-RDW8D-xx	100-277V	50-60	8W	880	≥80	120°	3000, 4000, 5000K	24"	UL, RoHS, DLC
HUT14-RDW13D-xx	100-277V	50-60	13W	1,780	≥80	120°	3000, 4000, 5000K	48"	UL, RoHS, DLC
HUT14-RDW16D-xx	100-277V	50-60	16W	1,750	≥80	120°	3000, 4000, 5000K	48"	UL, RoHS, DLC
HUT14-RDW20D-xx	100-277V	50-60	20W	2,200	≥80	120°	3000, 4000, 5000K	48"	UL, RoHS, DLC

* "xx" Represents Color Temperature: "30" = 3000K / "40" = 4000K / "50" = 5000K

*Dimensions and specifications subject to change without notice