



Project:	
Type:	
Catalog#:	

G8 Series LED Area / Shoebox luminaires are architecturally designed for parking lots, walkways, building exteriors, security lighting and other outdoor general lighting applications.

General Data

Fixture Type	Area Light
Technology	High Lumen LED Light Source
Finish	Dark Bronze
CCT	5000K
Distribution	Type III Standard (Type IV,V Options available)
Material-Housing	Die-Cast Aluminum
Material- Lens	Impact Resistant Polycarbonate Optical Lens
Rated Hours	50,000 Hours Avg Lifetime
Warranty	5 Years
Certifications	cULus, DLC Premium, RoHS
Working Temp.	-20°F to 104°F
IP Rating	IP65 / Wet Location
Dimensions	20.5" (L) x 13.2" (W) x 3.6" (H)

Electrical & Performance Data

Nominal Wattage	150W
Input Voltage	120-277VAC
Power Factor	>0.95
THD	<20%
Lumen Output	19,500
Lumen Efficacy	130lm/w
CRI	>70
Dimmability	0-10V Dimmable
Surge Protection	10kV

*Dimensions and specifications subject to change without notice.



CAT#: G8ASB-3150W-50

Features & Benefits

- **HI-Efficiency Integral Driver**
- **HI-Lumen SMD chipset / 50,000+ hour lifespan**
- **IP65 Wet Location Rated**
- **Adjustable Angle Mounts Standard**
- **LM79/LM80/TM-21 data available**
- **Type IV & V Distribution available. Consult Factory.**
- **480VAC Version available. Consult Factory.**
- **Motion Sensor available. Consult Factory.**

Mounting Options Part No.

Round Pole Slip Fit	G8ASB-SFT
Sq Pole Arm	G8ASB-ASQ
Round Pole Arm	G8ASB-ARD
Trunnion	G8ASB-TRN

Sensor Options Part No.

Photocell	G8ASB-PC
-----------	----------

