



Project:	
Type:	
Catalog#:	

START Lighting's Commercial Downlight Retrofit units are designed for universal fit into most existing 6" Commercial Housings. With high efficacy, durability and lightweight construction these are ideal for new and retrofit commercial applications. Delivers consistent superior lighting while reducing operation and labor costs. Simple and flexible installation. Energy efficiency savings, lasts longer than traditional downlights, and backed by our 5 Year Warranty

**General Data**

Fixture Type	Commercial Downlight
Technology	High Lumen LED Light Source
Finish	White Trim
CCT (Field Tunable)	3000K, 3500K, & 4000K
Distribution	70°
Material-Housing	Aluminum
Material- Lens	Frosted Polycarbonate Diffuser
Rated Hours	50,000 Hours Avg Lifetime
Warranty	5 Years
Certifications	cULus, Energy Star, RoHS
Working Temp.	14°F to 104°F
IP Rating	IP20 / Damp Location
Dimensions	7.68" (Trim OD) x 6.06"OD(Reflector) x 5.91"(H)

**Electrical & Performance Data**

Nominal Wattage	15W, 23W, & 30W (Tunable)
Input Voltage	120-277VAC
Power Factor	≥0.90
THD	<25%
Lumen Output	1,275 – 2,550
Lumen Efficacy	85lm/w
CRI	≥80
Dimmability	0-10V Dimmable
Surge Protection	2.5kV

\*Dimensions and specifications subject to change without notice.



**CAT#: DCDL6-RJW1530E-VJ**

**Features & Benefits**

- CCT & Wattage Tunable
- Suitable for BOTH Retrofit and New Construction applications
- Flicker-free, 0-10V Dimmable Driver
- High Efficacy LED chipset / 50,000 hour lifespan
- Consumes up to 50% less energy than standard fluorescent lamps
- Minimized labor costs
- LM79/LM80/TM-21 data available
- 6" Housing available. Consult Factory.

**Sensor Options      Part No.**

External OCC Sensor      **DCDL-OCC**

**Emergency Options      Part No.**

EM Battery Backup      **FHEM-05**

