



Project:	
Type:	
Catalog#:	

Designed for new build and retrofit applications, START's Tunable Volumetric Troffer Luminaires with Tunable CCT & Tunable Power provide greater flexibility to allow field customization at the flick of a switch. Our Troffer Luminaires are simple to install, provide superior lighting and offer in-field customization for most applications.

**General Data**

Fixture Type	Volumetric Troffer Light
Technology	High Lumen LED Light Source
Finish	White
CCT	3500K - 4000K - 5000K (Tunable)
Distribution	110°
Material-Housing	Aluminum Heatsink / Steel Housing
Material- Lens	Durable Polycarbonate Diffuser
Rated Hours	50,000 Hours Avg Lifetime
Warranty	5 Years
Certifications	cETLus, DLC Premium, RoHS
Working Temp.	-4°F to 105°F
IP Rating	IP20 / Damp Location
Dimensions	23.75" (L) x 23.75" (W) x 1.85" (H)

**Electrical & Performance Data**

Nominal Wattage	25W - 30W - 35W (Tunable)
Input Voltage	120-277VAC
Power Factor	>0.95
THD	<20%
Lumen Output	3,250 – 4,550
Lumen Efficacy	130lm/w
CRI	>80
Dimmability	0-10V Dimmable
Surge Protection	1.5kv

\*Dimensions and specifications subject to change without notice.



**CAT#: DMTRP-RDW2535D-VJ**

**Features & Benefits**

- Switch-Type Field Tunable CCT
- Switch-Type Field Tunable Power
- Rugged Steel Housing and Aluminum Heatsink
- Isolated, Non-Flicker driver
- High power SMD chipset / 50,000+ hour lifespan.
- Consumes up to 50% less energy than standard fluorescent lamps
- Minimized labor costs
- LM79/LM80/TM-21 data available
- 0-10v Dimming

<b>EM Options</b>	<b>Part No.</b>
External EM Backup	<b>FHEM-05</b>

